

DEFECT DETECTION ON ELECTRICAL  
POWER EQUIPMENT USING  
THERMAL IMAGING  
TECHNOLOGY

GEOFFREY ASIEGBU OGADIMMA

A thesis submitted in fulfillment of the requirement for the award of the degree of  
Master of Engineering in Electrical Engineering

Faculty of Electrical and Electronics Engineering  
UNIVERSITI MALAYSIA PAHANG

January 2013

## UNIVERSITI MALAYSIA PAHANG

**DECLARATION OF THESIS AND COPYRIGHT**

Author's full name : GEOFFREY OGADIMMA ASIEGBU

Date of birth : 15/08/1973

Title : DEFECT DETECTION ON ELECTRICAL POWER  
EQUIPMENTS USING THERMAL IMAGING TECHNOLOGY

Academic Session : 2012/2013

I declare that this thesis is classified as :

- ☐ **CONFIDENTIAL** (Contains confidential information under the Official Secret Act 1972)\*
- ☐ **RESTRICTED** (Contains restricted information as specified by the organization where the research was done)\*
- ☒ **OPEN ACCESS** (I agree that my thesis be published as online open access Full text)

I acknowledge that Universiti Malaysia pahang reserve that right as follows:

1. The Thesis is the Property of Universiti Malaysia Pahang.
2. The Library of Universiti Malaysia Pahang has the right to make copies for the purpose of research only.
3. The has the right to make copies of the thesis for academic exchange.

Certified By

\_\_\_\_\_  
(Student's Signature)

\_\_\_\_\_  
(Signature of Supervisor)

A09006352  
New IC / Passport Number  
Date:

DR. MOHD RAZALI BIN DAUD  
Name of Supervisor  
Date:

**NOTES**

:\*If the thesis is CONFIDENTIAL or RESTRICTED please attach with the letter from the organization with period and reasons for confidentiality and restriction.

### **SUPERVISORS' DECLARATION**

We hereby declare that we have checked this project and in our opinion, this project is adequate in terms of scope and quality of the award of the degree of Master of Engineering in Electrical Engineering.

Signature :  
Supervisor : DR. MOHD RAZALI BIN DAUD  
Position : SENIOR LECTURER  
Date : 27/06/2013

Signature :  
Co-supervisor : ASSO. PROF. DR. KAMARUL HAWARI BIN GHAZALI  
Position : SENIOR LECTURER  
Date : 27/07/2013

### **STUDENT'S DECLARATION**

I hereby declare that the work in this thesis is my own other than quotations and summaries, which have been duly acknowledged. This project has neither been accepted for any degree nor concurrently submitted for award of another degree.

---

OGA

Signature :  
Name : GEOFFREY ASIEGBU OGADIMMA  
ID Number : MEE11003  
Date : 27/06/2013

<b>TABLE OF CONTENTS</b>	<b>PAGE</b>
<b>DECLARATION OF THESIS AND COPYRIGHT</b>	ii
<b>SUPERVISOR'S DECLARATION</b>	iii
<b>STUDENT'S DECLARATION</b>	iv
<b>DEDICATION</b>	v
<b>ACKNOWLEDGEMENTS</b>	vi
<b>ABSTRACT</b>	vii
<b>ABSTRAK</b>	viii
<b>TABLE OF CONTENTS</b>	ix
<b>LIST OF TABLES</b>	xii
<b>LIST OF FIGURES</b>	xiii
<b>LIST OF SYMBOLS</b>	xv
<b>LIST OF ABBREVIATIONS</b>	xvi

## **CHAPTER 1 INTRODUCTION**

1.1	Introduction	1
1.2	Fundamental Problem	1
1.3	Research Problem Addressed to Electrical Equipment	3
1.4	Recommended Solution	4
1.5	Objectives of Research Project	5
1.6	Scope of Research Project	5
1.7	Thesis Outline	6

## **CHAPTER 2 LITERATURE REVIEW**

2.1	Introduction	7
2.2	Terminology	7
2.3	What is Thermography?	8
2.4	Why Thermography is Important?	8
2.5	Qualities of A Good IRT Image	8
2.6	The Electromagnetic Spectrum	9

2.7	Infrared Radiation	9
2.8	Radiometric Temperature	10
2.9	Reflectivity	10
2.10	Ambient Temperature	10
2.11	Review of Thermal Defect Detection Analysis	10

### **CHAPTER 3 RESEARCH METHODOLOG DEFECT DETECTION SYSTEM DESIGN**

3.1	Introduction	23
3.2	Supervised Optimal Threshold Selection Technique	30
3.3	RGB Optimal Threshold Segmentation Algorithm	36
3.4	Measurement of Segmentation Operation	41
3.5	Performance Measure of Defect Detection Algorithm	44
3.6	Evaluation of Sensitivity of Defect Detection System	48
3.7	Classification of Extracted Thermal Regions	49
3.8	Comparative Study on Electrical Equipment Defect Detection Technique	56

### **CHAPTER 4 RESULTS AND DISCUSSIONS**

4.1	Introduction	60
4.2	Tools and Image Acquisition	60
4.3	Quality Image Acquisition	60
4.4	Defect Detection Evaluation	62
4.5	Results of RGB Optimal Threshold Algorithm	63
4.6	Interpretation of Classified Regions	67
4.7	Decision-making, Sensitivity, and Accuracy Results	74
4.8	Results of K Means Clustering Algorithm	81
4.9	Defect Detection Comparison Study Results	92

### **CHAPTER 5 CONCLUSION AND RECOMMENDATIONS**

5.1	Introduction	103
5.2	Achievement	105
5.3	Recommendation for future work	106

<b>REFERENCES</b>	107
<b>APPENDICES</b>	114
A	Table A Ti25 Fluke Thermal Imager Specification 114
B-1	Table B-1 Emissivity Values for Metals 115
B-2	Table B-2 Emissivity Values for Non Metals 116
C-1	Tools And Materials 118
C-2	Thermal Picture Acquisition 118
C-3	Factors for Measurement Accuracy 120
C-4	Internal Calibration of Camera 121
C-5	Factory Calibration of Camera 121
C-6	Emissivity Correction 121
C-7	Reflected Temperature Compensation 122
C-8	Distance-To-Spot Size Ratio 123
C-9	Instantaneous Field of View (IFOV) 124
C-10	Minimum Distance for Focus 125
C-11	Correction Measurement 125
D	List of Publications 126

## LIST OF TABLES

<b>Table No.</b>	<b>Title</b>	<b>Page</b>
3.1	Experimental thermal inspection result	29
3.2	Optimal threshold values (low temperature equipment)	45
3.3	Optimal threshold values (medium temperature equipment)	45
3.4	Optimal threshold values (high temperature equipment)	45
3.5	Low temperature equipment classification ( $\Delta T \geq 40^{\circ}\text{C}$ )	49
3.6	Medium temperature equipment classification ( $\Delta T \geq 65^{\circ}\text{C}$ )	50
3.7	High Temperature Equipment Classification ( $\Delta T \geq 105^{\circ}\text{C}$ )	50
3.8	Standard analysis report base on temperature difference ( $^{\circ}\text{C}$ )	51
3.9	Comparison between measured results, mathematical evaluation and international maintenance testing standards	53
4.1	Sensitivity, predictive positive value (PPV) and false positive rate (FPR) (low temperature equipment)	78
4.2	Sensitivity, predictive positive value (PPV) and false positive Rate (FPR) medium temperature equipment	79
4.3	Sensitivity, predictive positive value (PPV) and false positive Rate (FPR) high temperature equipment	79
4.4	Description of thermal inspection of electrical facilities and accuracy	80
4.5	Comparison analysis result table	101



## LIST OF FIGURES

<b>Figure No.</b>	<b>Title</b>	<b>Page</b>
3.1	Visual spectrum photos and normal view of electrical facilities	25
3.2	Ambient reference temperature from de-energized and energized electric motor thermogram	26
3.3	Segments of backgrounds and foregrounds IRT images	28
3.4	Transformer IRT image; (a = Non-normalized IRT image), (b = Non-normalized grayscale IRT image), (c = Non-normalized IRT image histogram), (d = Normalized IRT image), (e = Normalized grayscale IRT image), (f = Normalized IRT image histogram)	32
3.5	Circuit breaker IRT image; (a = Non-normalized IRT image), (b = Non-normalized grayscale IRT image), (c = Non-normalized IRT image histogram), (d = Normalized IRT image), (e = Normalized grayscale IRT image), (f = Normalized IRT image histogram)	32
3.6	Real-time inspected electrical facilities	41
3.7	Ideal receiver operating characteristics curve	42
3.8	Area under convex hull	43
3.9	Original IRT image, (b) True Negative (TN), (c) True Positive (TP)	43
3.10	Original IRT image, (b) Result of flawed threshold, (c) Result of optimal threshold	44
3.11	Defect detection training flow process	52
3.12	Computer aided defect detection scrutiny system final flow process	55
3.13	K-means clustering algorithm flowchart	58
4.1	Well-focused and flawed IRT images; (a = Electric Motor), (b = Contactor), (c = Capacitor), (d = Transformer),	62

	(e = Circuit Breaker)	
4.2	Typical fault of overload or loose connection; (a = normal view), (b = thermal spectrum view), (c = Image Histogram)	64
4.3	Screen print of Matlab processed results (a = Abnormal thermal condition), (b = Abnormal thermal condition), (c = Normal thermal condition), (d = Warming thermal condition), (e = Abnormal thermal condition), (f = Warming thermal condition), (g = Warming thermal condition).	67
4.4	Thermogram of electrical components at warming stage (A = Molded case circuit breaker IRT image), (B = Electric motor bearing IRT image), (C = Electric motor IRT image), (D = Connector IRT image).	70
4.5	Thermogram of electrical components under critical condition (A = Bolted joint and connector IRT image), (B = Distribution transformer IRT image), (C = Distribution transformer IRT image), (D = Dry type transformer IRT image), (E = Circuit breaker IRT image).	74
4.6	RGB optimal threshold classification result of abnormal transformer	75
4.7	RGB optimal threshold classification result of high thermal fuse box	75
4.8	RGB optimal threshold classification result of warm thermal condition electric motor	76
4.9	RGB optimal threshold classification result of normal thermal condition minitured circuit breaker	77
4.10	RGB optimal threshold classification result of electric motor within ambient temperature	77
4.11	Results of unsupervised k-means clustering algorithm	85
4.12	Results of supervised K means classification	91
4.13	Defect detection comparison results; (a = RGB optimal threshold algorithm), (b = K-means clustering algorithm).	100

## LIST OF SYMBOLS

$\mu_r, \mu_g, \mu_b$	Mean value of red, green, blue colors in the IRT image
$r_i, g_i, b_i$	Pixel value of red, green, blue colors in the IRT image
$N$	Total Number of image pixels of the IRT image
$\sigma_r^2, \sigma_g^2, \sigma_b^2$	Variance values red, green, blue color components in the IRT image
$\sigma_{rg}^2, \sigma_{rb}^2, \sigma_{gb}^2$	Covariance values of pixel similarity between color combinations in the IRT image
$e$	Exponential Function Applied in Gaussian PDF
$\pi$	Pi = 3.1429 (constant)
$\Delta T$	Temperature difference between equipment and ambient
$\Delta t$	Temperature difference between similar equipment
$N_{gv}$	Normalized grayscale value
$T_i$	Optimal threshold value of each extracted regions

## LIST OF ABBREVIATIONS

RGB	Red, Green, Blue color model or space
IRT	Infrared Thermal Image
ROC	Receiver Operating Characteristics
TN	True Negative
TP	True Positive
FN	False Negative
FP	False Positive
PPV	Predictive Positive Value
FPR	False Positive Rate
$TPR_{value}$	Actual pixel value but does not represent real thermal value
$TH_{real}$	Real equipment thermal value

## ABSTRACT

Electrical power equipment and components are vital constituent portions of human existence. They are found virtually in every domestic home and manufacturing industries. These electrical power equipment, operates at a temperature above absolute zero, certainly emit infrared radiation. In some power distribution systems, existing station equipment could no longer withstand the short circuit current capacity causing equipment break down. The electrical equipment failures can be avoided if the temperature threshold is detected in order to take timely corrective action. Quality control and part inspection have done considerably well in the area of manufacturing but not yet gotten to its fully robust thermal imaging technology application. Thermal image is a term comes from the infrared thermography. It has gained its popularity in the last few decades over other predictive maintenance techniques due to its many advantages such as contact-less, easy to interpret the thermal data, large area of inspection as well as free from dangerous radiation. This research project proposed defect detection on electrical power equipment using thermal imaging technology. The aim is to study the thermal characteristic of electrical power equipment, secondly, to design defect detection technique and make a fault decision as well as comparing results with other defect detection techniques and international thermal evaluation standard. A thermal imager is used to acquire thermal images of the tested electrical facilities under various operating conditions. The thermal image in RGB color space is normalized and morphologically dissected using image mean, variance, and covariance which is applied on the mixtures of Gaussian Probability Distribution Function (GPDF) through which threshold values were determined. Using the threshold values similar pixels are connected via maximum likelihood criterion been function of short circuit OR logic operator. The predetermined threshold values are optimized using Receiver Operating Characteristic (ROC) curve and the area under convex hull. Regions of electrical thermogram are segmented using the optimal threshold values. Various features in the infrared thermal (IRT) image are extracted in order to detect anomalies. Classification and decision are made in terms of colors and temperature difference values. Matlab image processing software is used to implement these procedures. Application of this system is quite simple, user friendly, time and cost effective. In conclusion, a total of 111 different electrical power distribution facilities was experimentally inspected. Within the limits of experimental errors, the results of the analysis showed that 99.9% sensitivity and 99.72% accuracy was achieved with an error rate of 0.28 that was attributed to mistakes due to over and less caution during experimental thermal inspection of electrical facilities. The results suggested that, the method provides an accurate identification of defective parts can be extended for further applications. The results also suggest that the system works well enough to help improve the value and efficiency of consumable electrical power equipment reducing the number of faults in the power distribution line, ensuring safety of the workers and users of electricity, protecting electrical power facilities from damage due to over-heating or fire. Above all, testing, inspection and preventive maintenance work become safer, easier, and faster with a reasonably high degree of accuracy with this result-oriented defect detection scrutiny system on electrical power facilities.

## ABSTRAK

Peralatan kuasa elektrik dan komponennya merupakan konstituen penting kewujudan manusia. Mereka dijumpai hampir di setiap rumah domestik dan industri pembuatan. Peralatan kuasa elektrik, beroperasi pada suhu di atas sifar mutlak, sudah tentu mengeluarkan sinaran inframerah. Dalam sesetengah sistem pengagihan kuasa, peralatan yang sedia ada tidak dapat lagi menahan kapasiti arus litar pintas yang menyebabkan peralatan rosak. Kerosakan peralatan elektrik boleh dielakkan jika ambang suhu dikesan untuk mengambil tindakan pembetulan yang tepat pada masanya. Penggunaan pengimejan haba di dalam bidang kawalan kualiti dan pemeriksaan komponen dalam bidang pembuatan adalah agak baik tetapi belum mencapai tahap automatik sepenuhnya. Imej haba adalah istilah yang berasal dari termografi inframerah. Ia telah mendapat populariti dalam beberapa dekad yang lalu berbanding teknik-teknik penyelenggaraan ramalan lain kerana banyak kelebihan seperti kurang-sentuhan, mudah untuk mentafsirkan data haba, kawasan pemeriksaan yang besar serta bebas daripada sinaran berbahaya. Projek penyelidikan ini mencadangkan pengesanan kerosakan pada peralatan kuasa elektrik menggunakan teknologi pengimejan haba. Tujuannya adalah untuk mengkaji ciri-ciri haba peralatan kuasa elektrik, dan untuk mereka bentuk teknik pengesanan kerosakan serta memberitahu pengguna bahagian yang mengalami kerosakan. Keputusan yang dikeluarkan oleh projek ini akan dibandingkan dengan lain-lain teknik pengesanan kerosakan dan standard penilaian haba antarabangsa. Kamera pengimejan haba digunakan untuk memperolehi imej haba daripada peralatan elektrik digunakan di dalam pelbagai keadaan operasi. Imej haba dalam ruang warna RGB dinormalkan dan dipecahkan secara morfologi menggunakan imej min, varians dan kovarians yang digunakan pada campuran Gaussian Kebarangkalian Pengagihan Fungsi (GPDF) di mana nilai-nilai ambang ditentukan. Piksel yang mempunyai nilai-nilai di dalam lingkungan nilai ambang akan disambungkan melalui kriteria kebolehdarian maksimum bagi fungsi litar pintas ATAU operator logik. Nilai ambang yang telah ditetapkan dioptimumkan menggunakan keluk "Receiver Operating Characteristic (ROC)" dan kawasan di bawah cembung badan. Pelbagai ciri dalam imej haba inframerah (IRT) imej yang diambil diekstrak untuk mengesan anomali. Klasifikasi dan keputusan dibuat dari segi warna dan nilai perbezaan suhu. Fungsi pemprosesan imej di dalam Matlab digunakan untuk melaksanakan prosedur ini. Penggunaan sistem ini adalah agak mudah, mesra pengguna, masa dan kos efektif. Ujian dijalankan ke atas sebanyak 111 peralatan elektrik yang berbeza. Dalam had kesilapan eksperimen, keputusan analisis menunjukkan bahawa 99.9% kepekaan dan ketepatan 99.72% telah dicapai dengan kadar kesilapan 0.28 yang telah dikaitkan dengan kesilapan kerana kurang atau terlalu berhati-hati semasa pemeriksaan terma eksperimen kemudahan elektrik. Keputusan menunjukkan bahawa, kaedah menyediakan pengenalan tepat bahagian yang rosak boleh dilanjutkan bagi permohonan yang selanjutnya. Keputusan juga menunjukkan bahawa sistem kerja-kerja yang cukup baik untuk membantu meningkatkan nilai dan kecekapan guna peralatan kuasa elektrik mengurangkan jumlah kerosakan dalam talian pengagihan kuasa, memastikan keselamatan pekerja dan pengguna elektrik, melindungi kemudahan kuasa elektrik daripada kerosakan yang disebabkan oleh kepada lebih-pemanasan atau api. Paling penting, ujian, pemeriksaan dan kerja-kerja penyelenggaraan pencegahan menjadi lebih selamat, lebih mudah, dan lebih cepat dengan tahap yang cukup tinggi ketepatan dengan ini kecacatan berorientasikan hasil pengesanan sistem penelitian mengenai kemudahan elektrik.

## LIST OF REFERENCES

- Abbott J.A. 1999. *Quality measurements of fruits and vegetables*. 15. **207**. Postharvest. Biol.Technol.
- Abbott J.A., Lu R., Upchurch B.L., Stroshine R.L. 1997. Technologies for nondestructive quality evaluation of fruits and vegetables. *Horticultural reviews*. J. Janick Wiley. **20**. Chichester, U.K.
- Ahmed M. A. Haidar, Geoffrey O. Asiegbu, Kamarul Hawari, Faisal A. F. Ibrahim, 2012. Electrical defect detection in thermal image. *Advanced Materials Research*, **433-440**. 3366-3370.
- Alan G. Glaros, Rex B. Kline. 1988. Understanding the accuracy of tests with cutting scores. *Journal of Clinical Psychology*, **44**(6).
- Anil Z. Chitade, Dr S.K. Katiyar. 2010. Color based image segmentation using K-means clustering. *International Journal of Engineering Science and Technology*, **2** (10):5319-5325.
- Blagojce Stojcevski, Akhtar Kalam. 2010. Fault location in overhead power lines using the iec61850. *International Protocol International Review on Computers and Software (IRECOS)*, **3**(5): 888-899.
- Braunovic, M., Myshkin N.K., and Konchits V.V. 2007. *electrical contacts fundamentals, applications and technology*. Paul G. Slade. Poland: CRC Press.
- Brian J. McPartland, Frederic P. Hartwell and Joseph F. McPartland. 2011. *National electrical code handbook*. (Ed.). 27th. USA: McGraw-Hill.
- Brunner, C.C., Maristany, A.G., Butler, D.A., VanLeeuwen, D., Funck, J.W. 1992. An evaluation of color spaces for detecting defects in Douglas-fir veneer. *Industrial Metrology* 2 (3/4), 169\_ 184.
- Butler, D.A., Brunner, C.C., Funck, J.W. 1989. A dual-threshold image sweep-and-mark algorithm for defect detection in veneer. *Forest Products Journal* 39(5): 25-28.
- Butz P., Hofmann C., Tauscher B. 2005. Recent developments in non-invasive techniques for fresh fruit and vegetable internal quality analysis. *J Food Science* **70**, 131.
- Carosena Meola. 2007. Infrared thermography of masonry structures. *Elsevier Journal Publication on Infrared Physics & Technology* **49**:228–233.
- Chan Y. C., Fan Yeung, Guangchang Jin, Naikong Bao, and Chung P. S. 1995. Non-destructive detection of defects in miniaturized multilayer ceramic capacitors using digital speckle correlation techniques. *IEEE Transactions on Computers, Packaging and Manufacturing Technology-Part A*.

- Chen X., Jing H., Tao Y., Carr L., Wheaton F. 2003. Real-time detection of physical hazards in de-bonded poultry using high resolution X-ray imaging. *Proceedings of the ASAE/CSAE Annual International Meeting*, Las Vegas, Paper #033084.
- Chen, W. L., So, A. T. P., Lai, L. L. 2000. Three-dimensional thermal imaging for power equipment monitoring. *Proceedings IEEE Conference on Generation, Transmission, & Distribution*, **147**(6):355-360.
- Chuck, H. 2001. *Handbook of Nondestructive Evaluation*. McGraw-Hill Professional.
- Chunli F., Fengrui S., and Li Y. 2005. Investigation on nondestructive evaluation of pipelines using infrared thermography. *IEEE International Conference Terahertz Electronics*, **2**:339-340.
- Churtin C., Ignatushin A. 1999. On-line & offline diagnostics for power station HV equipment. *IEEE International Conference on Electrical Insulation, Electrical Manufacturing, and Coil Winding*, 637-643.
- Connors, R.W., McMillin, C.W., Ng, C.N. 1985. The utility of color information in the location and identification of defects in surfaced hardwood lumber. *Proceedings of the First International Conference on Scanning Technology in Sawmilling*. Miller- Freeman Publications, San Francisco, CA, pp. XVIII-1\_ XVIII-33.
- D.F. Bodies. in Food. 2007. M. Edwards. Woodhead Publishing Company, Cambridge.
- Don A. Genutis. 2007. Infrared Inspections and Applications. *NETA World*, (online) <http://www.netaworld.ld.org>
- Electric Power Engineering Center. 2007. Guide to Power Transformer Specification Issues. University of Canterbury. (online) <http://www.scribd.com/doc/65031914/EPECentre-Guide-to-Transformer-Specification-Issues>
- Etehad M., Tavakol & S. Sadri & E. Y. K. Ng. 2008. Application of k- and fuzzy c-means for color segmentation of thermal infrared breast images. *Springer Science, Business Media, LLC*.
- Faisal Shafaita, Daniel Keysersa, Thomas M. Breuelb. Efficient Implementation of Local Adaptive Thresholding Techniques Using Integral Image. (online). <http://code.google.com/p/ocropus/> 2008.
- Fluke. (online) <http://thermalimagingblog.com/index.php/tag/fovmeasurement/>
- Fournier D. and Amyot N. 2001. Diagnostic of overheating underground distribution cable joints. *IEE Conference Electricity Distribution*, **1**(482):18-21.
- Franz Pernkopfa, Paul O'Leary. 2003. Image acquisition techniques for automatic visual inspection of metallic surfaces. *NDT&E International*. **36**: 609 - 617.



- Funck, J.W., Zhong, Y., Butler, D.A., Brunner, C.C., Forrer, J.B.. 2003. Image segmentation algorithms applied to wood defect detection. *Journal Publication on Computers and Electronics in Agriculture*, **41**: 157- 179.
- Gautam Biswas, Ravi Kapadia, Xudong W. Yu. 1997. Combined qualitative–quantitative steady-state diagnosis of continuous-valued systems. *IEEE Transactions on Systems, Man, and Cybernetics—Part A: Systems and Humans*.
- Graves M., Batchelor B.G., Palmer S.C. 1994. *Three-dimensional X-ray inspection of food products*. A. G. Tescher. **248**. Applications of digital image, in Applications of Digital Image Processing XVII”, SPIE Proceedings 2298.
- Graves v, Smith A., Batchelor B.G. 1998. Approaches to foreign body detection in foods. *Trends. Food Sci. Technol.*
- Hafizan Mat Som, Jasni Mohamad Zain and Amzari Jihadi Ghazali. 2011. Application of threshold techniques for readability improvement of jawi historical manuscript images. *Advanced Computing International Journal (ACIJ)*.
- Hamed Shah-Hosseini, Reza Safabakhsh. 2002. Automatic multilevel thresholding for image segmentation by the growing time adaptive self-organizing map. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.
- Hani, A., Almohair, K., Abd Rahman Ramli, Elsadig, A.M., Shaiful, B., Hashim, J. 2007. Skin detection in luminance images using threshold technique. *International Journal of Imaging Science and Engineering (IJISE)*, GA,USA,ISSN:1934-9955,Vol.1; No.1.
- Hari Kumar Singh, Shiv Kumar Tomar, Prashant Kumar Maurya. 2012. Thresholding techniques applied for segmentation of RGB and multispectral images. *Proceedings published by International Journal of Computer Applications® (IJCA)*- 7-8.
- Hideaki Sato, Yasue Mitsukura, Minoru Fukumi, Norio Akamatsu. 2003. Thresholds decision method for fast object detection systems. *Proceedings of IEEE International Symposium on Computational Intelligence in Robotics and Automation*, Kohe, Japan.
- Infrared Training and Infrared Certification Standard for infrared inspection of electrical systems & rotating equipment, Infraspction Institute, 2008 Article.
- Infraspction Institute. 2008. Standard for infrared inspection of electrical systems & rotating equipment. In: Infraspction Institute, *Infrared Training and Infrared Certification*. 425 Ellis Street Burlington, NJ 08016, USA.
- Jaspreet Kaur, Sinha, H.P. 2012. Automated localization of optic disc and macula from fundus images. *International Journal of Advanced Research in Computer Science and Software Engineering*.
- Jayas D.S., Karunakaran C., Paliwal J. 2004. Grain quality monitoring using machine vision and soft X-ray for cereal grains. *Proceedings of the International Quality Grains Conference, Indianapolis*.

- Jessy G. Smith, B Venkoba Rao, Vivek Diwanji, Shivaram Kamat. 2009. Fault diagnosis – isolation of malfunctions in power transformers. *Tata Consultancy Services Limited*, 10 June 2009.
- Jha S.N., Matsuoka T. (Res.) 2000. Non-destructive techniques for quality evaluation of intact fruits and vegetables. *Food Sci. Technol.*
- Jia Li , James Z. Wang , Gio Wiederhold. 2000. Integrated region matching for image retrieval (IRM). *Proceedings of The Eighth ACM International Conference on Multimedia*, 147-156.
- Jifeng Ning, LeiZhang, DavidZhang, ChengkeW. 2010. Interactive Image Segmentation by Maximal Similarity Based Region Merging. *Pattern Recognition* **43**:445 – 456
- Jim White, 2008, Electrical inspections using thermal imaging. Fluke Corporation. U.S.A. 6/2008 3358415 A-EN-N Rev A.
- Jin Li, Pyanwei Wang, P Hong Liang, P Jie Weip, Dada Wang, P Hong Yu. 2012. X-Ray Image Defects Detection Algorithm Based on Digital Silhouette, *International Journal of Digital Content Technology and its Applications (JDCTA)*.
- Jonas Boberg. 2008. Early fault detection with model-based testing. *Proceedings of the Sigplan Workshop on Erlang*
- José Martínez, Rodolfo Lagioia Edenor S.A. – Argentina Edenor S.A. 2007. Experience Performing Infrared Thermography in the Maintenance of a Distribution Utility. *19th International Conference on Electricity Distribution*. Vienna.
- Jung-Shiong Chang, Hong-Yuan Mark Liaob, Maw-Kae Herb, Jun-Wei Hsieh, Ming-Yang Cherna. 1997. New automatic multi-level thresholding technique for segmentation of thermal images. *Image and Vision Computing* **15**:23-34.
- L. M. Lavie. 2004. Electrical safety for an offshore power system. *IEEE Potentials*, **23**:(3):39-42.
- Leemans, V., Magein, H., Destain, M.F. 1998. Defects segmentation on ‘Golden Delicious’ apples by using color machine vision. *Journal Publication on Computers and Electronics in Agriculture*, **20**:117–130.
- Li, H., and Burgess, A. E., 2010. Evaluation of signal detection performance with pseudo-color display and lumpy backgrounds. *J Med Syst* 34:35–42 41 In: KundelH. L. (Ed.), SPIE, medical imaging: Image perception, 3036:143–149.
- Liju Dong, Ge Yub, Philip Ogunbona, Wanqing Li. 2008. An efficient iterative algorithm for image thresholding. *Pattern Recognition Letters* **29**:1311–1316.
- Lim K.S., Barigou M. 2004. X-ray micro-computed tomography of cellular food products. *Food Res. Int.* **37**:1001.

- Lindquist T.M., Bertling L., Eriksson R. 2005. Estimation of disconnectors contact condition for modeling the effect of maintenance and ageing. *Power Tech IEEE Conference, Russia*.
- Mair v. 1988. Industrial robotics. *Prentice Hall*, New York.
- Majed Jabri, Housseem Jerbi, Naceur Benhadj Braiek. 2010. Fault detection of synchronous generator based on moving horizon parameter estimation and evolutionary computation. *International Review on Computers and Software (IRECOS)*, **3** (1): 38-47.
- Martin Technical Electrical Safety & Efficiency. 2012. Infrared Thermography Inspection. [http://www.marttechnical.com/infrared\\_inspections/electrical\\_infrared\\_inspection\\_service.php](http://www.marttechnical.com/infrared_inspections/electrical_infrared_inspection_service.php)
- Matian M., Marquis A.J., Brandon N.P. 2010. Application of Thermal Imaging to Validate a Heat Transfer Model for Polymer Electrolyte Fuel Cells. *International Journal of Hydrogen Energy*, **35**:12308-12316.
- McGarry S.L. 1984. Acceptable quality levels are not acceptable any more. *Proceedings of Autofact*, 15:1 – 13.
- Mehmet Sezgin, Biilent Sankd. 2001. Selection of thresholding methods for non-desctructive testing applications. *Image Processing, Proceedings ieeexplore*.
- Mehmet Sezgin, Bu" lent Sankur. 2004. Survey over image thresholding techniques and quantitative performance evaluation. *Journal of Electronic Imaging* **13**(1):146–165.
- Mohd Shawal Jadin, Soib Taib, Shahid Kabir, Mohd Ansor Bin Yusof. 2011. Image processing methods for evaluating infrared thermographic image of electrical equipment. *Progress In Electromagnetics Research Symposium Proceedings*, Marrakesh, Morocco.
- Mythili Thiruganam, S.Margret Anouncia, Sachin Kantipudi. 2010. Automatic defect detection and counting in radiographic weldment images. *International Journal of Computer Applications*. **10**(2):0975 – 8887.
- Nicholas Radaa, Gregory Tripletta, Samuel Graham. 2007. High-speed thermal analysis of high Power diode arrays. *Solid-State Electronics ISDRS*, College Park, MD, USA.
- Prasoon Srivastava. 3<sup>rd</sup> February 2010. Zero defect policy is a culture. (online) <http://www.ciol.com/News/Interviews/Zero-Defect-Policy-is-a-culture/3210130972/0/>
- Rada N., Triplett G., Graham S., Kovaleski S. 2008. High-speed thermal analysis of high power diode arrays. *Solid-State Electronics ISDRS*, **52**. Issue 10:1602–1605.
- Rajib Kumar Jha, Biswas P. K., Chatterji B. N. 2010. Image segmentation using suprathreshold stochastic resonance. *World Academy of Science, Engineering and Technology* **72**.
- Robert M. Button. 2005. Soft-Fault Detection Technologies Developed for Electrical Power Systems. (online) <http://powerweb.grc.nasa.gov/electsys/>

- Ronald P. Haff, Natsuko Toyofuku. 2008. X-ray detection of defects and contaminants in the Food industry.
- Rudi Heriansyah, S.A.R.Abu-Bakar. 2009. Defect detection in thermal image for non-destructive evaluation of petrochemical equipment. *NDT&E International* **42**: 729–740
- Sangwook Lee, Color Image-based Defect Detection Method and Steel Bridge Coating, *ASC Annual International Conference Proceedings*, 2011
- Shawal M., Taib S., Kabir S., Ansor M. 2011. Image processing methods for evaluating infrared thermographic image of electrical equipment. *Progress in Electromagnetics Research Symposium Proceedings*, Morocco, 1299-1302.
- Slawomir Grys. 2012. New thermal contrast definition for defect characterization by active thermography. *Elsevier Journal Publication on Measurement*.
- Smith B. 1993. Making war on defects: six sigma design. *IEEE Spectrum*, **30**(9): 43 – 47.
- Snell J., and Renowden J. 2000. Improving results of thermographic inspections of electrical transmission and distribution lines. *Proceedings IEEE International Conference Transmission and Distribution Construction*, 135-144.
- Soriano M., Huovinen S., Martinkauppi, Laaksonen. 2000. Skin detection in video under changing illumination conditions. *In Proceedings 15th International Conference on Pattern Recognition*. **1**:839– 842.
- Tayyaba Azim, Arfan Jaffar, Anwar.M.Mirza. 2011. Automatic skin detection in luminance images using threshold technique. *International Conference on Computer Engineering and Applications 2009 IPCSIT* **2**.
- Techniques and Select Industrial Applications of Thermal Imaging. 2011. (online) [http://www.ndted.org/EducationResources/CommunityCollege/Other%20Methods/IRT/IR\\_Applications.htm](http://www.ndted.org/EducationResources/CommunityCollege/Other%20Methods/IRT/IR_Applications.htm)
- Timothy S. Newman, Anil K. Jain. 1995. A survey on automated visual inspection. *computer vision and image understanding*. **61**(2):231 – 262.
- Vadivel A, Majumdar A K, Shamik Sural. 2003. Performance comparison of distance metrics in content-based Image retrieval applications. *Proceedings of International Conference on Computer Vision Application*.
- Wagner G.G.. 1987. Combining X-ray imaging and machine vision, in optics, illumination, and Image sensing for machine vision II. D.J. Svetkoff. **850**. SPIE Proceedings.
- Wahab, Md Saidin. 2003. Defect detection in high pressure die casting product using image processing technology. Master Thesis. University of South Australia, Australia.

- Wei Zhan, Junkai Yang. 2012. Real time and automatic vehicle type recognition system design and its application. *International Conference on Mechanical Engineering and Automation Advances in Biomedical Engineering*.
- Wenbing Tao, Hai Jin, Liman Liu. 2007. Object segmentation using ant colony optimization algorithm and fuzzy entropy. *Journal Publication on Pattern Recognition Letters* **28**:788–796.
- Wen-Nung Lie. 1995. Automatic Target Segmentation by Locally Adaptive Image Thresholding. *IEEE Transactions on Image Processing*.
- Wong, K. C. P.; Ryan, H. M. and Tindle, J. 1996. Power system fault prediction using artificial neural networks. *International Conference on Neural Information Processing*, Hong Kong.
- Wretman, D., 2006. Finding regions of interest in a decision support system for analysis of infrared images. Master Thesis, Royal Institute of Technology. Stockholm, Sweden.
- Yang Cao, Xiaoming Gu, Qi Jin. 2008. Infrared technology in the fault diagnosis of substation equipment. *Technical Session 1 Distribution network equipment*, Shanghai Electric Power Company Shanghai Branch Southern Power, 200030, SI-17 CP1377, CICED.
- Ying-Chieh, Chou Leehter Yao. 2009. Automatic diagnosis system of electrical equipment using infrared thermography. *International Conference of Soft Computing and Pattern Recognition*.
- Yingzi Du, Chein Chang, Paul David Thouin. 2004. Unsupervised approach to color video thresholding. *Optical Engineering*.
- Yinxiao Liu. 2009. A new method of threshold and gradient optimization using class uncertainty theory and its quantitative analysis. Master Thesis, University of Iowa, Canada.
- Yong Wu, Yuanjun He, Hongming Cai. 2005. Optimal threshold selection algorithm in edge detection based on wavelet transform. *Elsevier Journal Publication on Image and Vision Computing* **23**:1159–1169.
- Youngbae Hwang, Jun-Sik Kim, Inso Kweon. 2006. Determination of color space for accurate change detection. *Proceedings of the International Conference on Image Processing, ICIP*. Atlanta, Georgia, USA.
- Yu. P. Aksyonov, A. Golubev, A. Mochortov, V. Rodionov, V. Minein, B. Romanov, C. Churtin, A. Ignatushin. 1999. On-line & offline diagnostics for power station HV equipment. *IEEE Int. Conf. Electrical Insulation, Electrical Manufacturing, and Coil Winding*, 26-28:637-643.
- Željko Hocenski, Suzana Vasilić, Verica Hocenski. 2006. Improved canny edge detector in ceramic tiles defect detection. *IEEE Industrial Electronics, IECON 2006 - 32nd Annual Conference*, 3328 – 3331.

## APPENDIX D

### LIST OF PUBLICATIONS

Geoffrey O. Asiegbu, Ahmed M. A. Haidar, Kamarul Hawari, “Thermal Defect Analysis on Transformer Using a RLC Network and Thermography,” *Circuit and Systems*, 2013, 4, 52-60 doi:10.4236/cs.2013.41058.

Geoffrey O. Asiegbu, Ahmed M. A. Haidar, Kamarul Hawari, “Non-Destructive Defect Detection on Electrical Equipment Using Thermographic Technology,” *International Reviews on Computers and Software (I.RE.CO.S)*. Vol. 7, N. 3 may 2012. ISSN 1828-6003. (6.13 I.F.)

Ahmed M. A. Haidar, Geoffrey O. Asiegbu, Kamarul Hawari, Faisal A. F. Ibrahim, “Electrical Defect Detection in Thermal Image,” *Advanced Materials Research Vols.* 433-440 (2012) pp 3366-3370

Geoffrey O. Asiegbu, Ahmed M. A. Haidar, Kamarul Hawari, “A Review of Defect Detection on Electrical Equipment Using Image Processing Technology,” 4th International Conference on Signal and Image Processing. *Lecture Notes in Electrical Engineering*, 221 DOI:10.1007/978-81-322-0997-3\_23 ©Springer India 2013.

Geoffrey O. Asiegbu, Ahmed M. A. Haidar, Kamarul Hawari, Defect Detection on Electrical Equipment, Malaysian Conference on Electrical, Electronic and Control Technology (MCEECT 2012), University Malaysia Pahang, February 16, 2012.

Geoffrey O. Asiegbu, Ahmed M. A. Haidar, “Defect Tracking of Electrical Components,” United Kingdom-Malaysia-Ireland Engineering Science International Conference, (UMIES 2011) University Malaya, Kuala Lumpur, 12-14 July 2011.